

36 Sedan Setup

1. Install props and drain plug.
2. Remove fiberglass shipping top from cabin top. Also remove shrink wrap from bridge. Remove tape and clean areas where bridge will set. Check for voids along the top of the windows.
3. On bridge remove panel under aft seat base and take off port aft access panel.
4. Apply sealant (white sikaflex # 8105901) around deck where bridge will set, including the top of patio door. Apply sealant just prior to setting bridge.
5. The lifting points for bridge are between the two stands-offs on the forward and aft bridge rails.
6. Position bridge over boat. Run appropriate wires thru aft starboard corner; and appropriate wires thru aft port corner.
7. Set bridge in place, making sure that no wires get caught or pinched off. Make sure the bridge is pushed all the way forward.
8. With the bridge in place:
 - a. Screw it down around the bridge opening.
 - b. Install screws above the cockpit patio door.
 - c. Install two screws on each side of the aft end of the bridge behind the bridge drain covers.
 - d. Also, apply white sikaflex sealant (in Mac Kit # 8105901) to each screw before installing it.
9. Install anchor light to top of arch. Make sure to seal hole where wire comes thru. Make sure to use Tuff Gel on fasteners. Cosmetically seal around base of anchor light.
10. Connect wires in aft starboard seat base and aft port corner of bridge. Run shift and throttle cable and steering lines to helm and hook up. After testing, screw starboard seat base panel in. Reinstall port aft access plate.
11. Install the helm and companion seats onto their bases. Also install aft seat bench cushions.
12. Cosmetically seal aft bridge to cabin top seam.
13. Install white drip cap above patio door. Making sure to use silicone on screws and cosmetically around cap.
14. Backfill Bridge to deck seam with white silicone # 8101200.
15. Put small amount of sealant in each hole for plastic fasteners, line up fasteners on bolster with holes on valance, and then pound each fastener in place until bolster is tight to ceiling. Install forward bolster above windshield than aft bolster and than side bolsters.
16. Install the port and starboard pilaster and curtain rods and curtains.
17. Install canvas bow set and canvas (*if it was ordered*).